

TOSHIBA

e-STUDIO3025AC

e-STUDIO3525AC

e-STUDIO4525AC

e-STUDIO5525AC

e-STUDIO6525AC

Colour Multifunctional Printers

- Multifunctional A3 colour systems with an outstanding document output at a speed of up to 65 pages per minute
- Large and fully customisable user interface for enhanced efficiency and tailored workflows
- Easy integration into modern business environments, including cloud and mobile printing



**TOGETHER
INFORMATION**

Specifications

e-STUDIO3025AC/3525AC/4525AC

e-STUDIO5525AC/6525AC

General	
Print & Copy Speed	A4: 30 / 35 / 45 ppm A3: 16 / 18 / 22 ppm
Warm-up Time ~	12 seconds from low power mode 20 seconds from low power mode
Paper Size & Weight	Drawer 1: A5R-A3, 60-300 g/m ² Drawer 2: A5R-A3 / A5R-320 x 460 mm, 60-300 g/m ² Bypass: Single Feed: 100 x 148 mm-A3, 52-300 g/m ² Banner paper (up to 305 x 1,200 mm, 90-163 g/m ²)
Paper Capacity	Drawer : 2 x 550 sheets Bypass: 1 x 100 sheets Max. 5,200 sheets
Automatic Duplex	A5R-A3, 60-256 g/m ²
Controller Type	Toshiba e-BRIDGE Next
Control Panel	26 cm (10.1") Multi-Touch Colour Panel
Memory	4 GB 6 GB
Security SSD (Standard/Max)	128 GB / 640 GB
Interface	10Base-T/100Base-TX/1000Base-T, High Speed, USB 2.0, WLAN* (IEEE802.11b/g/n), Bluetooth*, Wi-Fi Direct
Dimension & Weight	585 x 586 x 787 mm (W x D x H), ~77kg 585 x 641 x 787 mm (W x D x H), ~79 kg
Print	
Resolution	600 dpi x 600 dpi, 5bit. PS Driver: 1200 dpi x 1200 dpi & 3,600 (Equivalence) x 1200 dpi
Page Description Language	PCL5e, PCL5c, PCL6 (PCL XL), XPS, PDF and PS3, JPEG
Supported Systems	Windows 11/10/8.1, Windows Server2022/2019/2016/2012 R2/2012 (64bit), Mac OS 10.12-12, Linux/Unix, Citrix, SAP, AS/400
Network Protocols	TCP/IP (IPv4/IPv6, NetBios over TCP/IP)
Mobile Printing	e-BRIDGE Print & Capture, Mopria® Print Service, AirPrint on iOS or macOS®
Print Functions	Universal Printer Driver, Driver Templates, Driver plug-ins*, Print from USB, Hold Print, Tandem Printing, E-Mail direct printing
Scan	
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
Scan Speed	Reversing Automatic Document Feeder*: up to 73 ipm (300 dpi) in colour and monochrome Dual Scan Document Feeder*: up to 240 ipm (300 dpi) in colour and monochrome
Scan Modes	Auto-Colour (ACS), Colour, Greyscale, Monochrome
File Formats	"JPEG, Multi/Single Page TIFF/XPS/PDF, Secure PDF, Slim PDF, PDF/A, PDF/A-2, Searchable PDF* (and other formats like DOCX, XLSX)""
Scan Functions	"WS Scan, Scan to USB, Scan to E-Mail, Scan to File, (SMB, FTP, FTPS, IPX/SPX, Local), Meta Scan*, OCR scan, Scan to Box (e-Filing), WIA, TWAIN"
Copy	
Resolution Scan:	600 x 600 dpi
Print: equiv.	2,400 x 600 dpi (with smoothing)
First Copy Output Time	(30 & 35 ppm) 5.9 sec. (mono) / 7.8 sec. (colour) (45 ppm) 4.4 sec. (mono) / 5.7 sec. (colour) (55 & 65 ppm) 4.3sec. (mono) / 5.6 sec. (colour)
Multiple Copying	Up to 999 copies
Copy Modes	Text/Photo, Text, Photo, Custom
Copy Functions	Electronic Sort, Rotate Sort, ID Card Copy, Edge Erase, 2-in-1 / 4-in-1 mod
FAX	
Communication	Super G3, G3 - (opt. 2nd line) Internet Fax T.37
Transmission Speed	3 seconds per page
Compression	JBIG, MMR, MR, MH
Fax Memory	1 GB Transmission/Reception
Network-Fax	Driver for Windows 11/10/8.1, Windows Server2022/2019/2016/Server 2012 R2/Server 2012 (64bit)
Incoming Fax Routing	To shared folders (SMB, FTP), E-Mail, e-Filing
System & Security	
Device Management	e-BRIDGE CloudConnect (eCC) & Top Access for remote administrations & configurations
System Features	"e-Filing document server for secure storage, Document distribution and Print-on-Demand (one public box, 200 user boxes), 12,060 one-touch templates for storage of personalised settings and workflows, Scan/Fax Preview, Rip-while-Print, e-BRIDGE Open Platform, Embedded Web Browser, Job Skip, PCL Barcode printing, e-BRIDGE Plus Embedded Apps"
Accounting & Security	"Role Based Access, LDAP support, 1,000 department & 10,000 user codes, Card Reader*, Private Print, Scan to Secure PDF, Pull-printing* Standard data encryption with Security SSD, Data Overwrite function when optional HDD is chosen, IP and MAC address filter, Port Filter, Support of SSL and IPsec* protocols, IEEE802.1 x support, CC certified (ISO/IEC15408) with HCD-PP v1.0""



Distributed by

For more information please contact us:



PT. Spektrum Global Teknologi
www.spektrumgt.co.id

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation.

Copyright ©2025 TOSHIBA TEC.

